

REMOTE OPTIONS

Remote Key	---	---	---	---
Remote Disarm	NO	YES		
Armed Answer Rings	--	(0 to 15, default = 8)		
Disarmed Answer Rings	--	(0 to 15, default = 8)		
PC Modem	NO	YES		
Alarm Receiver Auth	NO	YES		
Service Receiver Auth	NO	YES		
Manufacturer Auth	NO	YES		
Allow Network Remote	NO	YES		
Network Programming Port	--	(Default = 2001)		
Encrypt Network Remote	NO	YES		
Allow Cellular Remote	NO	YES		
First GPRS APN	---	---	---	---
	(Default = SECURECOM400)			
Second GPRS APN	---	---	---	---
	(Default = SECURECOM400)			
Encrypt Cellular Remote	NO	YES		
Allow RS-232 Remote	NO	YES		
Entre Connection	NONE	NET		
Entre Incoming TCP Port	--	(Default = 2011)		
Entre IP Address	---	---	---	---
Entre Outbound TCP Port	--	(Default = 2001)		
Entre Backup IP Address	---	---	---	---
Entre Backup TCP Port	--	(Default = 2001)		
Entre Checkin Minutes	--	(0, 3-240 minutes, default = 0)		
Entre Passphrase	---	---	---	---
Send Local Changes	NO	NET	DD	
Remote Change IP	---	---	---	---
Remote Change Port	--	(Default = 2002)		
Remote Phone No	---	---	---	---

SYSTEM REPORTS

Abort Reports	NO	YES		
Restoral Reports	NO	YES	DISARM	
Bypass Reports	NO	YES		
Schedule Change Rpts	NO	YES		
Code Change Reports	NO	YES		
Access Keypads	1 2 3 4 5 6 7 8			
	9 10 11 12 13 14 15 16			
Ambush	NO	YES		
Panic Test (XR500N/E)	NO	YES		

SYSTEM OPTIONS

System	AREA	A/P	H/A	GST
Instant Arming	NO	YES		
Closing Wait	NO	YES		
Entry Delay 1	--	(30 to 250 sec, default = 30)		
Entry Delay 2	--	(30 to 250 sec, default = 60)		
Entry Delay 3	--	(30 to 250 sec, default = 90)		
Entry Delay 4	--	(30 to 250 sec, default = 120)		
Cross Zone Time	--	(4 to 250 sec, default = 4)		
Zone Retard Delay	--	(0 to 250 sec, default = 10)		
Power Fail Delay Hrs	--	(0 to 15 hours, default = 1)		
Swinger Bypass Trips	--	(0 to 6, default = 2)		
Reset SwngR Bypass	NO	YES		
Time Change	NO	YES		
Hours from GMT	--	(0 to 23, default = 6)		
Latch Supervisory	NO	YES		
Programming Language				
Primary Language	ENGLISH	SPANISH	FRENCH	
Secondary Language	NONE	ENG	SPN	FRN
User Language				
Primary Language	ENGLISH	SPANISH	FRENCH	
Secondary Language	NONE	ENG	SPN	FRN
Bypass Limit	--	(0 to 8, default = 0)		
Card Plus PIN (XR500E)	NO	YES		
Wireless House Code	--	(0, 1 to 50, 99, default = 0)		
Detect Wireless Jamming	NO	YES		
Wireless Audibles	ANY	DAY	MIN	
Enable Keypad Panic Keys	NO	YES		
Occupied Premise	NO	YES		
Enhanced Zone Test	NO	YES		
Send 16 Character Names	NO	YES		
Keypad Armed LED	ALL	ANY		
Use False Alarm Question	NO	YES		

BELL OPTIONS

Bell Cutoff Time	--	(0 to 99 minutes, default = 15)		
Automatic Bell Test	NO	YES		
Bell Output	---	---	---	---
Bell Action . . .				
Fire Zones	Steady	Pulse	Temporal	None
Burglary Zones	Steady	Pulse	Temporal	None
Supervisory Zones	Steady	Pulse	Temporal	None
Panic Zones	Steady	Pulse	Temporal	None
Emergency Zones	Steady	Pulse	Temporal	None
Auxiliary 1 Zones	Steady	Pulse	Temporal	None
Auxiliary 2 Zones	Steady	Pulse	Temporal	None

OUTPUT OPTIONS

Cutoff Output		1 2 3 4 5 6		
Cutoff Time	--	(0 to 99 minutes, default = 0)		
Comm Fail Output	---	Ready Output	---	---
Fire Alarm Output	---	Phone Trouble Output	---	---
Fire Trouble Output	---	Late to Close Output	---	---
Panic Alarm Output	---	Device Fail Output	---	---
Ambush Output	---	Sensor Reset Output	---	---
Entry Output	---	Closing Wait Output	---	---
Exit Output	---	Arm-Alarm Output	---	---

