

# Thinline™ LCD Keypads

7060INT/7063INT/7073INT



## FEATURES

- ▶ Visual and audible alarm notification
- ▶ Silence alarm while system remains armed
- ▶ Optional integrated proximity reader
- ▶ Four optional onboard fully programmable zones
- ▶ Retrofit to any DMP panel

### ENHANCED OPTIONS

- ▶ 7063-WINT and 7073-WINT keypad proximity readers accept the DMP card format or up to eight different card formats

- ▶ Attractive Thinline keypad housing available in white
- ▶ Large, 32-character, Liquid Crystal Display (LCD)
- ▶ Custom 16-character home or business name
- ▶ Keypad and logo backlighting turns Red in alarm conditions
- ▶ User-adjustable brightness, tone and volume controls
- ▶ Supports "Is this a false alarm?" and Cancel/Verify™ features
- ▶ Built-in diagnostics for ease of service
- ▶ Simple harness connection to four-wire keypad bus
- ▶ Connect devices directly to keypad zones
- ▶ View system events/user activity through keypad display
- ▶ AC power and Armed LED
- ▶ Suitable for access and burglary applications
- ▶ Distinct burglary, zone monitor and prewarn tones
- ▶ Displays time of day, armed zones, and armed areas
- ▶ Optional backboxes for conduit or wall-mount applications
- ▶ Unique silence feature allows the user to silence alarm bells and still keep the system armed
- ▶ Compatible with all DMP panels

## VERSATILE SUPERVISED AND UNSUPERVISED OPERATION

When programmed for supervised operation, the keypad occupies its own unique device address on the keypad data bus.

Unsupervised operation allows you to install an unlimited number of keypads set to the same device address. Increasing the number of keypads allows maximum system operating flexibility.

## USER-FRIENDLY MENU FUNCTIONS

The User Menu allows you to quickly browse through menu options. Disarming and Arming functions are fast and easy. Any function allowed by the user authority level is simply accessed through the keypad, such as silencing alarms, resetting sensors or displaying events.

## TWO-BUTTON PANIC KEYS

The top row of keys can be used as two-button panic keys. The user simply presses and holds two of the keys simultaneously to send either a panic or non-medical emergency report to the monitoring center.

## “IS THIS A FALSE ALARM?” AND CANCEL/VERIFY

In a Home/Sleep/Away or All/Perimeter system, you can CANCEL a burglary alarm or VERIFY that a valid burglar alarm has occurred or answer whether it is a false alarm with YES or NO. Selecting VERIFY or YES manually verifies that an alarm occurred and sends an alarm verification message to the monitoring center.

## KEYPAD SHORTCUT KEYS

Keypad shortcut keys are provided to simplify operation and allow the user to more quickly arm, check in, monitor, exit or reset the system. One-button arming creates the simplest keypad available. Use the one-button shortcut keys for common functions, or use the ATM style menu for advanced functions, whichever method meets the user's needs or level of expertise with the system.

## END-USER CONTROL

Each of the Thinline Series keypads provides a simple User Options menu for adjusting brightness, speaker tone and volume.

## VALUABLE VISUAL ALARM INDICATOR

In a normal state, both the keypad and logo backlighting remain Green. However, during an alarm state, the keypad and logo turn Red. The change in color allows individuals on-site to instantly recognize an alarm condition.



Red Backlighting



Green Backlighting

## DISTINCT SOUND PATTERNS

The keypads also provide distinct sound patterns for burglary, zone monitor and prewarn that can help users identify the event occurring on their system.

## RETROFIT ANY EXISTING DMP SYSTEM

Retrofitting is quick and easy. Thinline keypads have the same footprint as existing DMP keypads and mount in currently installed backboxes. Thinline Series keypads require no special modules or panel upgrades. You can provide a new look and greater functionality to an existing system at just a fraction of the cost of all new equipment.

## MULTIPLE-KEYPAD SAVINGS

Install multiple keypads on the same wire run. Compatibility and cost savings make the Thinline Series an asset in every installation.

## OPTIONS

The Thinline Series also provide Keypad Options and Keypad Diagnostics menus available only to system installers and service technicians. Enter Keypad Options to set the keypad address and change the default keypad message.

Test the keypad operation at any time without disabling the system. The diagnostics program tests the LCD segments and backlighting, each of the 16 keyboard keys and the four zones on the 7073-WINT keypads.

## WEATHER INFORMATION

Up-to-date weather information for today and tomorrow will be displayed in the status list for cell or network connected panels. If the panel is not capable of supporting weather, the space will be blank. Eight statuses are available to indicate the weather: SUNNY, CLEAR, P-CLOUDY, CLOUDY, RAINY, SNOWY, STORMY and FOGGY.



# 7000 SERIES THINLINE™ KEYPADS

## UNIVERSAL PROGRAMMING TOOL

System installation and programming can be achieved without carrying around or purchasing expensive external programmers since panel and add-on module programming is integrated into DMP keypads.

Individually program panels and other programmable add-on modules directly from the keypad.

## 7073-WINT FOUR EXPANSION ZONES

Zone expansion is available right on the keypad where you need it the most. The four expansion zones on the 7073-WINT model are fully programmable Class B protection zones that can be used for a variety of burglary and access control applications.

## ZONE TYPE SELECTION

Keypad zones can be programmed using the same zone types available on the panel. Select supervised, unsupervised, night, panic, exit and emergency operation depending on the user requirements.

## ZONE DEVICE CHOICES

Connect PIRs, door and window contacts, pull stations, sprinkler tamper switches and silent panic buttons. Plan the installation to afford the best coverage while eliminating potential problems associated with multiple wire runs.

## 7063-WINT/7073-WINT CODELESS ARMING AND DISARMING

The innovative 7063-WINT and 7073-WINT Thinline keypads contain an onboard DMP proximity reader that allows users to simply present their proximity credentials to the keypad to gain access to a protected area. For compatibility with what your customers are using, you can customize up to seven concurrent card formats in addition to the DMP card format, although you're not required to have a DMP card format — you have the flexibility to use all eight.

## 7073-WINT MOMENTARY BYPASS

To provide an entry and exit window on systems with 24-hour perimeter protection, DMP offers the momentary bypass feature. Momentary bypass allows the user enough time to enter or exit the area. If the door remains open when the timer expires, a zone open/short is sent to the panel for the keypad Zone 2.

## 7073-WINT EXTERNAL READER

Add an external Wiegand-compatible reader to the 7073-WINT. This makes indoor/outdoor applications easy — or anywhere you need to add an external proximity or other technology reader.

## REQUEST-TO-EXIT (REX)

To enable easy user exit from an area, connect a motion sensing or mechanical device to Zone 3 on the keypad. As the user trips the zone, the keypad activates the door strike allowing the user to exit the area without presenting a card or entering a user code.

## PRIVATE LABELING

DMP offers dealers the option to present their company logos on the 7000 Series keypads. The logo displays on the rubber logo insert and replaces the DMP logo. The backlit logo glows Green during normal operation and turns Red in an alarm state.

Logo Location



# 7000INT SERIES THINLINE KEYPADS

## COMPATIBILITY REFERENCE SHEET

### Keypad Model Features

Model	Two-Button Panic	Red in Alarm	4-Zones	Internal Prox Reader	Wiegand Input Form C	Internal Door Strike Relay
7060-WINT	.	.				
7063-WINT	.	.		.		
7073-WINT	.	.	.	.		.

### Keypad Accessories

#### Alternate Housings

THIN-LCD-B/10	Black Housing, 10 Pk
THIN-LCD-I/10	Ivory Housing, 10 Pk
THIN-LCD-P/10	Platinum Housing, 10 Pk
THIN-LCD-W/10	White Housing, 10 Pk

#### Backboxes

695	Keypad Conduit Backbox
696	Keypad Backbox

#### Keypad Wiring Harness

300	4-Wire Harness
300-5	5-Wire Harness
300-12	12-Wire Harness
300-512	12-Wire Harness, 5' long

#### Proximity Credentials

1306	Prox Patch™
1306PW	Prox Patch
1326	ProxCard II® Card
1346	ProxKey III® Access Device
1351	ProxPass®
1386	ISOProx II® Card

#### External Proximity Readers (7073-WINT Only)

PP-6005B	ProxPoint® Plus Proximity Reader
MP-5365	MiniProx Proximity Reader
PR-5455	ProxPro® II Proximity Reader
MX-5375	MaxiProx® Proximity Reader
TL-5395	ThinLine II® Proximity Reader

### Farpointe Proximity Credentials

CSK-2	MIFARE DESFire EV1 Keyfob
CMC-2/10	CMC-2 Conekt Bluetooth Mobile Credential, 10 Pk
CMC-2/100	CMC-2 Conekt Bluetooth Mobile Credential, 100 Pk
PSC-1-H/10	Standard Light Proximity Card, 10 Pk
PSC-1-H/100	Standard Light Proximity Card, 100 Pk
PSC-3-H/10	Proximity Key Ring Tag, 10 Pk
PSK-3-H/100	Proximity Key Ring Tag, 100 Pk
PSM-2P-H/10	ISO Imageable Proximity Card, 10 Pk
DEZ/10	MIFARE® DESFire® EV1 Smartcard, 10 Pk
DEZ/100	MIFARE DESFire EV1 Smartcard, 100 Pk

### Farpointe Proximity Readers

CSR-35P	Conekt Bluetooth Reader
Delta 3	Contactless Mullion-Mount Smartcard Reader
Delta 5	Contactless Mullion-Mount Smartcard Reader
Delta 6.4	Contactless Smartcard Reader and Keypad
P-300-H-A	Cascade Proximity Reader
P-500-H-A	Alps Proximity Reader
P-620-H-A	Denali Proximity Reader with Keypad
P-640-H-A	Patagonia Proximity Reader with Keypad

### Ordering Information

7060-WINT*	Thinline LCD Keypad, White
7063-WINT*	Thinline LCD Keypad with Prox Reader, White
7073-WINT*	Thinline LCD Keypad with 4 Zones, Prox Reader and Door Access Relay, White

### Specifications

Operating Voltage	12 VDC
Dimensions	7" W × 5.25" H × 0.5" D
Display Type	LCD
Colors	White

### Compatibility

7000 Thinline Series keypads are compatible with all DMP panels.

### Current Draw

<b>7060-WINT</b>	
Standby	72 mA
Alarm	87 mA

### 7063-WINT

Standby	85 mA
Alarm	100 mA

### 7073-WINT

Standby	85 mA + 1.6 mA per active zone
Alarm	100 mA + 2 mA per active zone

### International Certifications

EN 50130-4:2011+A1:2014  
 EN 50130-5:2011  
 EN 50131-1:2006+A1:2009  
 EN 50131-3:2009  
 EN 60839-11-1:2013  
 EN 61000-3-2:2006+A1+A2  
 EN 61000-3-3:2013  
 EN 61000-6-4:2007

For additional information, go to [DMP.com](http://DMP.com)

800-641-4282 | [DMP.com](http://DMP.com)  
 2500 N. Partnership Blvd, Springfield, MO 65803  
 Designed, engineered & manufactured in  
 Springfield, MO using U.S. & global components

**LIMITED WARRANTY:** DMP warrants that the products manufactured by DMP and described herein shall be free from defects of manufacture, labeling, and packaging for a period of three (3) years from the invoice date to the original Buyer, provided that representative samples of the defective products are returned to DMP for inspection...To read the full DMP Limited Warranty, go to [DMP.com/Warranty](http://DMP.com/Warranty) or check the DMP Price List or Catalog.

\*RoHS Compliant