



## XR150 Panel



### FEATURES

- ▶ Onboard 10/100 network communication
- ▶ Plug-in CDMA, HSPA+, and LTE cellular communicators allow for Virtual Keypad™ app and central station connection
- ▶ Flash updateable: No more firmware chips to replace
- ▶ Adaptive Technology™ — Cost-effective supervised cellular backup
- ▶ Up to 100 DMP 1100 Series Wireless or wired LX-Bus
- ▶ Up to 99 schedules for areas, doors, outputs, holidays, Z-Wave® Favorites, and profiles

- ▶ Select Area, All/Perimeter, or Home/Sleep/Away operation
- ▶ Eight individual reporting areas with common areas
- ▶ Up to eight supervised door access-points and/or keypads
- ▶ 32-character names available for user, zone, area, profiles, and group names
- ▶ Up to four profiles per user
- ▶ Fully supervised 10/100 network and CDMA, HSPA+, and LTE cellular communication
- ▶ Communications diagnostics check network and cellular communication status from the keypad
- ▶ Eight communication paths between the panel and central station
- ▶ Flexible system arming features with Instant Arming option
- ▶ Lockdown operation from keypad or app
- ▶ Up to 130 two-wire smoke detector or fire-initiating zones
- ▶ 10,000 user codes with 99 profiles
- ▶ Mobile platform support via Virtual Keypad app
- ▶ 12,000 event buffer
- ▶ Built-in phone line monitor
- ▶ Multi-lingual menus available by user
- ▶ 1.5 Amps 12 VDC smoke and auxiliary output with OVC protection
- ▶ EASYconnect™ connection for the Virtual Keypad app when used with a network connection
- ▶ Guest House operation allows up to two separate protected systems



## FLEXIBLE COMMUNICATION

The XR150 has transitioned from dialer-focused communications to a true network, cellular, and Wi-Fi communications approach by providing stronger, multi-layered panel communications that ensure a constant link between the panel and central station.

The unique DMP Serial 3 format supports 32-character user, zone, and area names to decrease the central station response time and limit dependence on automation literal tables for message interpretation. Contact ID dialer format is also supported.

## NETWORK OR CELLULAR COMMUNICATION

Built-in 10/100 auto-sensing Ethernet connection enhances both standard and encrypted line security options. Both UDP and TCP are supported. The network option can be used as the primary or backup path to the digital dialer or cellular option.

The 263 Series Cellular Communicators can be used as the primary path, providing installation flexibility where no landlines are available. They can be used as a stand-alone communicator without the need for a backup. When used as the backup path, the 263 Series provides the security of a communication link that continues to function, even when landlines are cut or compromised. This interface works over a variety of carriers in the USA and Canada.

## ADAPTIVE TECHNOLOGY™

If a current primary communication path becomes unavailable, Adaptive Technology directs the panel to make a seamless transition from one communication path to another, ensuring that no check-in or supervision messages are missed. This allows a system to be fully supervised when the primary communication path is unavailable, while minimizing expensive cell traffic when all paths are good. The panel is constantly checking the failed path to enable the panel to revert back to the primary path when communication is restored.

## EASYconnect TECHNOLOGY

EASYconnect™ enables the control panel to establish an outbound connection to SecureCom Wireless™ over the network. This allows for an effortless installation of network panels, without any customer router programming, providing extremely quick app connection times.

## EIGHT COMMUNICATIONS PATHS

Create, configure, and manage up to eight communication paths between the panel and central station. Each path has its own panel communication programming parameters and can be identified as either primary or backup. This enables installers to configure a reliable communication link, offering greater confidence that the panel will always be connected to the central station.

## ACCESS CONTROL BURGLARY INTEGRATION

The XR150 is an integrated burglary, fire, and access control system that can be configured for users to gain access and disarm the area with a single card read.

## AREAS

Program up to eight areas with a variety of options, including independent arming. Each area has a unique name and may have its own account number.

Common areas automatically arm when the last independent area is armed and disarm when the first independent area is disarmed. This is ideal for lobbies or areas where users need common access to specific areas only.

## COMMUNICATION FUNCTION DIAGNOSTICS

The enhanced diagnostic menu enables technicians to check network and cellular communication status, and cell signal strength from the keypad.

## WIRELESS ONE-BUTTON KEYFOB WITH PROX

The 1145-1-BP is a wearable and portable panic button fob, programmable to function in multiple locations with alerts for lost fobs, late to test, and lower battery power.

## MOBILE PLATFORMS

DMP mobile platforms provide you with the tools you need to build strong connections with your customers. The Virtual Keypad™ app puts a keypad on the user's Apple iPhone®, iPad®, or Android™ compatible devices.

## FALSE ALARM FEATURES

Providing a way to reduce false alarms, both Cancel/Verify™ and the False Alarm Question prompt users to validate whether an alarm has occurred after entering their code. In a Home/Sleep/Away or All/Perimeter system, the user can either press Cancel/Verify or Yes/No to confirm alarm status and send it to the central station.

## DMP WIRELESS

DMP 1100 Series wireless communication employs 900 MHz frequency-hopping spread-spectrum to ensure clear and accurate signal transmissions without interference in practically any environment. Receivers are alerted of transmitters that go missing with two-way communication. Each wireless transmitter communicates with the receiver using supervision messages.

## LOCKDOWN

For emergency situations, a Lockdown command can be issued from the keypad menu or via remote command to lock all doors designated as public.

## TEMPORARY CODES

Temporary codes are user codes that can be entered with a finite date and specific time to expire.

## ZONE EXPANSION

The XR150 provides up to 142 zones, programmable for burglary, fire, and access applications.

- ▶ 10 Onboard Zones
- ▶ Eight Keypads = 32 Zones
- ▶ One Built-In LX Bus (100 zones)

## MULTIPLE CHIME TONES

In Zone Information, you can assign one of three distinct tones to a Night or Exit zone to know easily and quickly by different tones where and when a zone is opened. This feature has true security applications both residentially and commercially.

## SIMPLE ZONE EXPANSION WITH THE 1154/1158 WIRELESS INPUT MODULES

When a DMP panel is installed in the same location as a non-DMP panel, the 1154 can easily and quickly convert up to four existing hardwired zones from the old panel into wireless zones, and the 1158 can convert up to eight. Existing wiring does not have to be re-run, and existing contacts can be reused with the new system.

## ONE-MAN WALK TEST

A special code is also available for installers to test the system. The One-Man Walk Test allows a single technician to check the panel response to burglary, fire, panic, and supervisory zones.

## OUTPUTS

The XR150 provides up to 106 outputs that can be activated by zone or system events, by schedule, through the User Menu, or when a card is presented. Output Groups allow multiple outputs to activate with a single event and/or can be assigned to a particular user profile.

## FLEXIBILITY IN SCHEDULES

Enhanced scheduling for areas, doors, outputs, and holiday schedules offer flexibility for your customers. Ninety nine programmable schedules are available and can be assigned to an area, door, or output. The same schedule may be assigned to more than one area, door, or output, making them reusable. A List key facilitates browsing through the list of stored names on the keypad.

- ▶ Up to eight schedules per profile
- ▶ Up to eight schedules per door
- ▶ Up to eight schedules per area
- ▶ Up to eight schedules per output
- ▶ Up to 40 holiday dates

## MULTI-LINGUAL DISPLAY OPTION

XR150 Series systems may be programmed to display the User Menu and Status Display text in multiple languages.

## REAL-TIME STATUS ENHANCES THIRD-PARTY INTEGRATION

Alarm systems are increasingly being integrated with environmental control and home automation systems. With real-time status information from zones, doors, and other outputs, XR150 Series panels are readily integrated with these third-party control and automation systems. See [dmp.com/Integration\\_Partners](http://dmp.com/Integration_Partners).

## KEYPAD SHORTCUT KEYS

Time-saving shortcut keys provide easy one-button access to system control for frequently used functions like system arming. The shortcut keys enable users to arm, monitor zones, test, or reset the system and perform a variety of other functions faster and easier. Shortcut keys include: All, Reset, Home, Chime, Perim, and Sleep.

## Z-WAVE® SUPPORT

Add up to 140 Z-Wave devices with the 738Z module for mobile control of lights, locks, and thermostats. Up to 20 favorites allow users to program multiple devices to respond to a single command or panel event like arming and disarming. Z-Wave devices can be controlled with the 7800 Touchscreen Keypad, MyAccess and Virtual Keypad.

## EIGHT INDEPENDENT ACCESS CONTROL DOORS

Any access control reader with a Wiegand output can be connected to the XR150 Series panel. Attached card reader controls up to eight different doors.

The XR150 system can restrict access by schedule, arming level, or other criteria. The specific reason for access denial can be displayed on the keypad, stored in events, sent to the central station, and DMP Advanced Reporting. Anti-passback feature is also available.

## THINLINE™ KEYPADS

The stylish and sleek 7000 Series Thinline™ LCD Keypads provide three two-button panic keys, AC power and armed LEDs, 32-character display, backlit logo and keyboard plus an internal sounder. The 7063 keypad also includes a built-in proximity reader for codeless arming and disarming.

## VALUABLE VISUAL ALARM INDICATOR

In a normal state, both the keypad and logo backlighting remain blue on Aqualite keypads or green on Thinline keypads. However, during an alarm state, the keypad and logo turn red. The change in color allows individuals on-site to instantly recognize an alarm condition.

## 7800/9800 SERIES GRAPHIC TOUCHSCREEN KEYPAD

Provides touchscreen control for all keypad functions. It has a slim profile in stylish gloss black or white finish with a 5-inch, full-color display.



## COMMERCIAL FIRE

The DMP XR150 is also approved for commercial fire applications. Integrate intrusion, access, and fire into a single application or use the XR150FC as a stand-alone commercial fire alarm control panel. See LT-1317 for more information.

## ZONE AUDIT DAYS

This is a valuable auditing tool to determine whether a zone or device has not been tripped within a certain number of days. Whether the system is armed or disarmed, up to 365 days can elapse without the zone being tripped. Each time the zone is tripped, the counter restarts. After the countdown expires, a fault message is sent, and the timer begins the countdown again as per the programmed days.

## USER INACTIVITY

The User Inactivity audit provides notification of user codes or credentials not used over a programmable period of time; for example, employees or service providers who haven't used their PIN code or access credentials during a defined period of time. This notification promotes the purging of user and access rights as a result of employee termination or service provider changes. This option is found in System Options Programming.

## COMPATIBILITY REFERENCE SHEET

### Keypads

630F	LCD Remote Fire Command
7000	Series Thinline Keypads
7000A	Series Aqualite Keypads
7800	Graphic Touchscreen Keypads
9060	Wireless Keypad
9063	Wireless Keypad w/ Prox Reader
9800	Wireless Touchscreen Keypads

### Expansion Modules

708	Bus Extender
710	Bus Splitter/Repeater
711	Single Zone Expansion
712-8	8-zone Expansion
714	4-zone Class B Expansion
714-8	8-zone Class B Expansion
714-16	16-zone Class B Expansion
715	4-zone 2-wire Smoke Expansion
715-8	8-zone 2-wire Smoke Expansion
715-16	16-zone 2-wire Smoke Expansion
716	Output Expansion, 4 Form C relays, 4 open collector outputs
717	Graphic Annunciator: 20 open collector outputs
736P	Radionics Interface
738A	Ademco Interface Module
738I	ITI Interface Module

### Cellular Communicators

263C	CDMA Cellular Communicator
263H	HSPA+ Cellular Communicator
263HCAN	HSPA+ Cellular Communicator Canada
263LTE-V	LTE Communicator for Verizon
263LTE-A	LTE AT&T (Coming Soon)

### Auxiliary Modules

860	Relay Output Module
865	Style W/X Notification Circuit Module
866	Style W Notification Circuit Module
867	LX-Bus Notification Circuit Module
869	Style D Initiating Circuit Module
893A	Dual Phone Line Module

### Power Supplies

505-12/LX	5 Amps @ 12 VDC
505-12L	5 Amps @ 12 VDC
505-12A	5 Amps @ 12 VDC

### Smoke/Heat Detectors

2W-BLX	Conventional Smoke
2WT-BLX	Conventional Smoke/Heat

### Intrusion Devices

Virtually any other standard intrusion detectors

### Access Control

734	Wiegand Interface Module
734N	Network Wiegand Interface Module
734N-WIFI	Wi-Fi Wiegand Interface Module
OP-08CB	REX Motion Detector
PB-2	Request-to-Exit Button Proximity Readers and Credentials DMP ProxPatch

### Central Station Receivers

SCS-1R	Security Control Receiver
SCS-105	Single-Line DMP Serial 3 Receiver compatible with receivers that accept Standard CID, DD, or DMP Serial 3 messaging (Virtual Receiver)
SCS-VR	Software-only solution that runs on a server for network IP and cellular communications

### DMP Wireless

1100X	Receiver
1100XH	High Power Receiver
1100R	Repeater
1101	Universal Transmitter, Internal and External Contacts
1102	Universal Transmitter, External Contact
1103	Universal Transmitter, External Contact
1106	Universal Transmitter, Internal and External Contact
1107	Micro Window Transmitter
1114	Four-Zone Expander
1115	Wireless Temperature Sensor and Flood Detector
1116	Relay Output
1117	LED Annunciator
1118	Remote Indicator Light
1119	Door Sounder
1121	Pet Immune PIR Motion Detector
1122	Wireless PIR
1126C	Ceiling Mount Curtain PIR
1126R	360 Ceiling Mount PIR
1127C	Wall Mount Curtain PIR
1127W	Wall Mount Wide Angle PIR
1129	Glassbreak Detector
1131	Recessed Contact
1135	Siren, 100 dB
1136	Wireless Remote Chime
1137	LED Emergency Light
1139	Bill Trap
1141	Wall Button
1142	Two-Button Hold-up Transmitter

1142BC	Two-Button Belt Clip Hold-up Transmitter
1144-4	Four-Button Key Fob
1144-2P	Two-Button Key Fob
1144-1P	One-Button Key Fob
1144-D	Dual-Button Key Fob
1148	Personal Pendant
1154	Wireless Four-Zone Input Module
1158	Wireless 8-Zone Input Module
1164	Smoke Detector with Synchronized Sounder
1164NS-W	Wireless Smoke Detector with No Sounder
1166	Wireless Smoke Detector Ring
1183-135F	Heat Detector (Fixed)
1183-135R	Heat Detector (Rate of Rise)
1184	Carbon Monoxide Detector

### Accessories

270	Network Transient Suppressor
277	Commercial Fire Buzzer Module
300	Four-wire Harness
303	Silence/Reset Push-Button
305	Plug-in Output Relay
306	Tamper Harness
307-S	Screw-On Tamper Switch
3012	Clip-On Tamper Switch
335	Intrusion Siren
370	Lightning Suppressor
374	Surge Voltage Suppressor
431	Output Harness
738Z+	Z-Wave Interface Module
861	Power Distribution Module
300-9800-4	Four-wire Replacement Harness

### Dealer Management

Dealer Admin  
Remote Link Programming Software

### End User Management

Virtual Keypad  
MyAccess  
VirtualKeypad.com™  
System Link™ End-User Management Software  
Entré™ Access Control Software

### System Specifications

#### Primary Power (included):

16.5 VAC 50 VA transformer

#### Secondary Power:

12 VDC Battery  
Models: 365, 366, 368 or 369

#### Output Rating:

Bell	1.5 Amps at 12 VDC
Smoke and Auxiliary	1.5 Amps at 12 VDC

#### Current Draw:

180mA

#### Enclosures:

Material	Cold-rolled steel
Model 350 (Gray or Red)	17.5" W × 13.5" H × 3.5" D
Model 350A (Gray)	17.5" W × 13.5" H × 3.75" D
Model 352X (Gray)	14.5" W × 32" H × 34" D
Model 341 (Gray)	12.75" W × 6.55" H × 3.15" D

### Listings and approvals

New York FDNY  
FCC Part 68  
FCC Part 15  
Underwriters Laboratories (UL) Listed  
UL Bank, Safe, and Vault  
UL Commercial Fire  
UL Standard Line Security  
UL Encrypted Line Security  
NIST Validated Certificate #2350 and #2595  
Underwriters Laboratories Canada (ULC) Listed  
California State Fire Marshal (CSFM)

For additional information, go to [DMP.com/Compliance](http://DMP.com/Compliance).

800.641.4282 | [DMP.com](http://DMP.com)  
2500 N. Partnership Blvd, Springfield, MO 65803  
Designed, Engineered & Manufactured in Springfield, MO using U.S. & global components